

HPC-3150

15" High-performance expandable panel PC, Intel® 6/7th LGA1151 Processor, PCI/PCIe extension



Features

- Intel 6/7th Core/Celeron/Pentium processor
- 15" industrial LCD panel and resistive touch
- Front panel meet IP65
- Support -10~50°C Wide temperature operating
- Optional 12~19Vdc input
- Optional Expansion WiFi, Bluetooth, 4G, 5G
- Support PCI/PCIe card



Specifications

System	
CPU	Intel 6/7th LGA1151 Core/Celeron/Pentium processor
Chipset	Intel H110
Memory	2 x SO-DIMM DDR4-2133 (up to 32GB)
Storage	1 x Full-size Mini-PCIe for mSATA SSD 1 x 2.5" driver bay for SATA3.0 HDD/SSD
Operating System	Windows 7/10, Linux
Display	
Size	15-inch
Resolution	1024 x 768
Brightness	350 cd/m ²
Contrast Ratio	1000:1
LED Lifetime	50000 hrs
Touch Screen	
Type	Industrial five-wire resistive touch
I/O Connectors	
Serial Port	2 x RS232 (up to 6 x RS232)
USB Port	2 x USB2.0
Ethernet	2 x GbE LAN
Audio	1 x Line-out, 1 x Mic-in, 2 x Speaker(8Ω2W)
Display	1 x HDMI, 1 x VGA
Power	1 x DC-in
Extensions	2 x PCI, 1 x PCIe(X4)
Other	1 x Romete SW

Power Specification	
Power Input	DC 12~19V
Consumption	According to the CPU
Environment	
Operating Temperature	-10~50°C
Relative Humidity	10%-90%, @ 40°C (non-condensing)
IP protection	IP65 (front panel)
Physical Characteristics	
Mounting Mode	VESA-mount, Panel-mount
Dimension (W x L x H)	370 x 294 x 100 mm
Weight	5.7Kg
Packing List	
Operating Temperature	1 x HPC-3150
	Power Adapter and Cord
	1 x Certificate
	1 x Warranty Card

Dimension

