

MIC-7511

Intel LGA 1151 6/7/8/9th CPU, 6 x Intel LAN, 2 x RS-232(1 x RS-232/485) , 6 x USB, 32 x GPIO



Product Features

- Intel LGA 1151 6/7/8/9th CPU
- 2 x RS-232(1 x RS-232/485)
- 6 x LAN, 6 x USB, 2 x DP, VGA
- 1 x 2.5" SATA HDD / SSD, 1 x M.2 SSD
- 32 x GPIO
- 24V DC Power Input

Specifications

| System | |
|------------------|--------------------------------------|
| Processor | Intel LGA 1151 6/7/8/9th CPU |
| Memory | 2 x DDR4 2133 MHz SO-DIMM up to 32GB |
| Graphics | By CPU |
| Operating System | Windows 7/8/10, Ubuntu |
| Storage | |
| Hard Disk | 1 x 2.5" SATA HDD / SSD |
| SSD | 1 x M.2 2280 SSD |
| I/O Connectors | |
| COM | 2 x RS-232(1 x RS-232/485) |
| USB | 2 x USB 2.0, 4 x USB 3.0 |
| LAN | 5 x Intel i210, 1 x Intel i219-LM |
| Video | 2 x DP, 1 x VGA |
| Audio | Line Out, Mic |
| GPIO | 32 x GPIO(FPGA) with Isolation |
| Remote Switch | 1 x 2Pin Remote Switch |
| Expansion | |
| PCI/PCIe | 1 x PCI, 1 x PCIe X16 |
| Mini PCIe | 1 x full-size mini PCIe |
| SIM | 1 x SIM(Inside) |
| USB KEY | 1 x USB2.0 TYPE A |
| Antenna hole | 2 x SMA-type |

| Power Management | |
|-----------------------|---------------------------|
| Power Input | DC 24V |
| Qualification | |
| Certifications | CE, FCC Class A |
| Environmental | |
| Operating Temp | -10 ~ 50°C(SSD) |
| Storage Temp | -40 ~ 80°C |
| Relative Humidity | 10 ~ 95% (Non-Condensing) |
| Mechanical | |
| Housing | Aluminum alloy |
| Mounting | Wall-mount |
| Dimension (W x D x H) | 220x256x136mm |
| Weight | 4.6kg |

Ordering Information

| Product number | Description |
|----------------|--|
| MIC-7511 | Intel LGA 1151 6/7/8/9th CPU, 6LAN, 2COM, 6USB, 32 x GPIO, 1 x PCI, 1 x PCIe X16 |

Dimensions

